Place of Origin: USA
Brand Name: Wilcoxon
Certification: CE
Model Number: 786A
Minimum Order Quantity: 1 set

Price: negotiated sale
Packaging Details: Standard
Delivery Time: 10-60days

Payment Terms:
 L/C, D/A, D/P, T/T, Western Union,

MoneyGram

Supply Ability: 5000 set/year



Product Specification

Wilcoxon Model: 787T

• Sensitivity: 100 MV/g 500 MV/g

Sensitivity Tolerance: ±5%

• Frequency Response ± 3

DB, Hz:

0.5 - 12,000

Resonance Frequency: 30 KHzMax Temperature: 120°C

Bias Output Voltage:
 Bias Output Voltage

• Electrical Noise 100 Hz: 5 μg/√Hz

• Highlight: Turbine equipment industrial vibration

monitoring

, Turbine equipment vibration transmitter, rustproof industrial vibration monitoring



Our Product Introduction

Product Description

Wilcoxon GENERAL PURPOSE Vibration sensor of Turbine equipment

Wilcoxon Sensing Technologies is a leading manufacturer and supplier of reliable, high-quality vibration monitoring products. Our solutions are at work in predictive maintenance and condition monitoring programs around the world. We design and manufacture a wide range of accelerometers, 4-20mA vibration transmitters and loop-powered sensors, velocity sensors, cable & connector assemblies, cementing pads and mounting studs, enclosures, handheld vibration meters and supportive instrumentation, and more. Our solutions are built to last, helping you effectively monitor rotating machinery in industrial, underwater and defense applications.

Vibration sensors for monitoring power plant machines

For power plant operators, avoiding outages and providing constant power supply are daily priorities. To keep plants operational, machines must be reliable. Wilcoxon vibration monitoring sensors are used by plant maintenance teams to provide advanced warning of component wear on power plant assets. Reliability engineers depend on vibration analysis/diagnostics to establish baseline, trend and early warning/detection of machine faults, plan for machine repairs, and optimize maintenance outages.

Typical power plant applications where vibration monitoring solutions are used include

Blowers, compressors, cooling towers Fans - forced draft and induced draft Hydro turbines (low frequency) Motors, nuclear machinery, pump

	r- r			
Wilcoxon 产品型号	•786A Series	•787A Series	786LF Series	•780A/B
灵敏度	100 mV/g 500 mV/g	100 mV/g 500 mV/g	100 mV/g 500 mV/g	100 mV/g
灵敏度公差	±5%	±5%	±5%	±5% /±10%
频率响应范围	0.5 - 14,000	0.5 - 10,000	0.1 - 13,000	0.5 - 14,000
±3 dB, Hz				
共振频率	30 kHz	22 kHz	30 kHz	30 kHz
电器噪音	5 μg/√Hz	5 μg/√Hz	3 μg/√Hz	5 μg/√Hz
100 Hz				
最高工作温度	120°C	120°C	120°C	120°C
偏置电压	12 VDC	12 VDC	13 VDC	12 VDC
接地	case isolated	case isolated	case isolated	case isolated
安装	1/4-28 tapped hole	1/4-28 captive screw	1/4-28 tapped hole	1/4-28 tapped hole
输出接头	2-pin MIL-C-5015 or 4-pin M12	2-pin MIL-C-5015 or 4-pin M12	2-pin MIL-C-5015	2-pin MIL-C-5015
合规	CE, API 670 •[CSA/ATEX/IECEx]	CE, API 670 •[CSA/ATEX/IECEx]	CE	CE, API 760 •[CSA/ATEX/IECE

Hizont (Shanghai) Industrial Technologies Co.,Ltd..



+86-15021164313



raymond@hyzont.com



powerplantmachine.com