



API 670 Compliant Industrial Accelerometer Sensor For Cement Manufacturing Machines

Our Product Introduction

Basic Information

- Place of Origin: USA
- Brand Name: Wilcoxon
- Certification: CE
- Model Number: 787A
- Minimum Order Quantity: 1 set
- Price: negotiated sale
- Packaging Details: Standard
- Delivery Time: 10-60days
- Payment Terms: L/C, D/A, D/P, T/T, Western Union, MoneyGram
- Supply Ability: 5000 set/year



Product Specification

- Wilcoxon Model: 787A
- Sensitivity: 100 MV/g
- Sensitivity Tolerance: $\pm 5\%$
- Frequency Response ± 3 DB, Hz: Dynamic Vibration (IEPE)
- Resonance Frequency: 0.5 Hz - 10,000 Hz
- Max Temperature: -55°C To +120°C
- Bias Output Voltage: Bias Output Voltage
- Grounding: Case Isolated
- Mounting: 1/4-28 Tapped Hole
- Output Connector: MIL-C-5015, 2-pin
- Compliance: CE •[CSA/ATEX/IECEX]
- Highlight: **API 670 Compliant Industrial Accelerometer Sensor**
, Cement Manufacturing Machines industrial accelerometer

for more products please visit us on powerplantmachine.com

Product Description

Vibration monitoring for cement manufacturing machines Industrial accelerometer sensor, 100 mV/g, low profile

Industrial accelerometer sensor features

API 670 compliant
Suitable for a wide range of industrial applications
Rugged design, hermetically sealed
ESD, overload, and reverse wiring protection

Included accessories

1/4-28 captive hex head screw

Industrial accelerometer sensor, 100 mV/g, low profile

Model 787A



Industrial accelerometer sensor, 100 mV/g sensitivity, $\pm 5\%$ sensitivity tolerance, low profile with side exit MIL-C-5015-style connector, 1/4-28 thread captive mounting screw, API 670 compliant

Specifications

PARAMETER	VALUE
Sensor output	Dynamic vibration (IEPE)
Sensitivity	100 mV/g
Sensitivity tolerance	$\pm 5\%$
Frequency response, ± 3 dB	0.5 Hz - 10,000 Hz
Mounting thread	1/4-28 captive screw
Connector style	MIL-C-5015, 2-pin
Connector orientation	Side exit
Full-scale range	80 g peak
Resonance frequency	22 kHz
Temperature range	-55°C to +120°C
Weight	145 grams
Hazardous area approvals	Non-approved; approved models available



+86-15021164313



raymond@hyzont.com



powerplantmachine.com

Room No.809-811 block No.1, Lane No.99 , Shenmei Road, Pudong New District, Shanghai, China.